



## U.S. Navy Selects CeramAlloy HTP & HTL (High Temperature Composites) to Repair Uptake Hatches on Vertical Missile Launch Systems



The U.S. Navy was in need of a solution to stop corrosion on their VLS (vertical launch system) uptake hatches on destroyer and cruiser class ships

were causing premature coating failure of the hatches.

Then two coats of CeramAlloy HTL were applied to resurface and protect the entire area.



Missiles are launched through open uptake hatches, usually located on the deck of a ship. The extreme high temperatures (400°F+), oxidized spent rocket fuel and environmental conditions of salt water

ENECON's high temperature resistant repair and rebuilding composite, CeramAlloy HTP, was used to repair and rebuild the severely eroded areas of each hatch. The HTP was then machined to maintain the required tolerances.

The Navy was so pleased with the first twelve pairs of uptake hatches, more will be protected in the near future.



Repairs made with CeramAlloy HTP



PROENECON SYSTEMS, S.A. · C/ Electricitat, 6. Pol. Ind. La Torre · 08760 - MARTORELL. Barcelona.  
·Telf: 93 211.15.30 · Fax: 93.253.11.31

Website: [www.proenecon.com](http://www.proenecon.com) · Email: [eneconib@proenecon.com](mailto:eneconib@proenecon.com)